# **Introduction to The Solr Enterprise Search Server**

# **Table of contents**

| 1 Solr in a Nutshell                                  | . 2 |
|---|-----|
| 2 Solr Uses the Lucene Search Library and Extends it! | 2   |
| 3 Detailed Features                                   | 2   |
| 3.1 Schema.   | . 2 |
| 3.2 Query   | 3   |
| 3.3 Core  |     |
| 3.4 Caching   | 3   |
| 3.5 Replication                                       |     |
| 3.6 Admin Interface                                   |     |

## 1. Solr in a Nutshell

Solr is a standalone enterprise search server with a web-services like API. You put documents in it (called "indexing") via XML over HTTP. You query it via HTTP GET and receive XML results.

- Advanced Full-Text Search Capabilities
- Optimized for High Volume Web Traffic
- Standards Based Open Interfaces XML and HTTP
- Comprehensive HTML Administration Interfaces
- Scalability Efficient Replication to other Solr Search Servers
- Flexible and Adaptable with XML configuration
- Extensible Plugin Architecture

# 2. Solr Uses the Lucene Search Library and Extends it!

- A Real Data Schema, with Dynamic Fields, Unique Keys
- Powerful Extensions to the Lucene Query Language
- Support for Dynamic Result Grouping and Filtering
- Advanced, Configurable Text Analysis
- Highly Configurable and User Extensible Caching
- Performance Optimizations
- External Configuration via XML
- An Administration Interface
- Monitorable Logging
- Fast Incremental Updates and Snapshot Distribution

#### 3. Detailed Features

## 3.1. Schema

- Defines the field types and fields of documents
- Can drive more intelligent processing
- Declarative Lucene Analyzer specification
- Dynamic Fields enables on-the-fly addition of fields
- CopyField functionality allows indexing a single field multiple ways, or combining multiple fields into a single searchable field
- Explicit types eliminates the need for guessing types of fields
- External file-based configuration of stopword lists, synonym lists, and protected word lists

## **3.2. Query**

- XML/HTTP and JSON/HTTP interfaces
- Highlighted context snippets
- Sort specifications added to query language
- Constant scoring range and prefix queries no idf, coord, or lengthNorm factors, and no restriction on the number of terms the query matches.
- Function Query influence the score by a function of a field's numeric value or ordinal
- Performance Optimizations

#### **3.3.** Core

- Pluggable query handlers and extensible XML data format
- Document uniqueness enforcement based on unique key field
- Batches updates and deletes for high performance
- User configurable commands triggered on index changes
- Searcher concurrency control
- Correct handling of numeric types for both sorting and range queries
- Ability to control where docs with the sort field missing will be placed
- Support for dynamic grouping of search results

#### 3.4. Caching

- Configurable Query Result, Filter, and Document cache instances
- Pluggable Cache implementations
- Cache warming in background
  - When a new searcher is opened, configurable searches are run against it in order to warm it up to avoid slow first hits. During warming, the current searcher handles live requests.
- Autowarming in background
  - The most recently accessed items in the caches of the current searcher are re-populated in the new searcher, enabing high cache hit rates across index/searcher changes.
- Fast/small filter implementation
- User level caching with autowarming support

#### 3.5. Replication

- Efficient distribution of index parts that have changed via rsync transport
- Pull strategy allows for easy addition of searchers

• Configurable distribution interval allows tradeoff between timeliness and cache utilization

## 3.6. Admin Interface

- Comprehensive statistics on cache utilization, updates, and queries
- Text analysis debugger, showing result of every stage in an analyzer
- Web Query Interface w/ debugging output
  - parsed query output
  - Lucene explain() document score detailing
  - explain score for documents outside of the requested range to debug why a given document wasn't ranked higher.