VistA System Monitor (VSM) 1.0 Technical Manual



August 2016

Department of Veterans Affairs (VA)

Office of Information and Technology (OI&T)

Enterprise Systems Engineering (ESE)

Capacity and Performance Engineering (CPE)

Revision History

Date	Revision	Description	Author
08/11/2016	1.0	Initial Document.	J L: St Petersburg
			Technical Writer: T. B.

Table of Contents

vision	History	¹	i
t of Fig	jures		iv
t of Ta	bles		۰۰۰۰۰۰۰۰۰۱
entatio	n		V
Pro	ocess	S Overview	1
1.1	Vist/	A Timed Collection Monitor (VTCM) Specific Process	1
1.			
1.	1.2		
1.	1.3		
1.2	Vist/		
1.		· · · ·	
1.	2.2	VSTM Metric Collection	
1.	2.3	VSTM Metric Transmission	4
File	es		5
		•	
2.2	VSM	·	
2.		Data Dictionary	
2.	2.2	Field Descriptions	7
2.3	VSM	CACHE TASK LOG File (#8969.03); Global: ^KMPV(8969.03	8
		Data Dictionary	
2.	3.2	Field Descriptions	8
2.4	^KM	PTMP("KMPV","VTCM"—Temporary Data Storage	9
2.	4.1	VTCM Usage of ^KMPTMP	9
2.	4.2	VSTM Usage of ^KMPTMP	9
Ro	utine	es	10
3.1	Vist.	A Timed Collection Monitor (VTCM) Specific Routines	10
3.2			
3.3		• , ,	
Fx			
		•	
		•	
_		•	
4.5		•	
	t of Figure 1 to f Ta ientation Pro 1.1	t of Figures t of Tables t of Tables entation Process 1.1 Vist/ 1.1.1 1.1.2 1.1.3 1.2 Vist/ 1.2.1 1.2.2 1.2.3 Files 2.1 VSM 2.1.1 2.1.2 2.2 VSM 2.2.1 2.2.2 2.3 VSM 2.3.1 2.3.2 2.4 ^KM 2.4.1 2.4.2 Routine 3.1 Vist/ 3.2 Vist/ 3.3 VSM Exporte 4.1 KMP 4.2 KMP 4.3 KMP 4.4 KMP	1.1.1 VTCM Monitor—Starting and Stopping 1.1.2 VTCM Metric Collection 1.1.3 VTCM Metric Transmission 1.2 VistA Storage Monitor (VSTM) Specific Process 1.2.1 VSTM Monitor—Starting and Stopping 1.2.2 VSTM Metric Collection. 1.2.3 VSTM Metric Transmission Files 2.1 VSM CONFIGURATION File (#8969); Global: ^KMPV(8969

iii

5	Arc	hiving	15
6	App	lication Programming Interfaces (APIs)	15
7	Exte	ernal Relationships	15
	7.1	Caché Task Manager	
	7.2	Dependencies	
	7.2	•	
8	Inte	rnal Relationships	17
		LIST TEMPLATE File (#409.61)	
	8.1		
	• • • • • • • • • • • • • • • • • • • •	PROTOCOL File (#101)	
	8.2		
	8.2		
	8.2		
	8.2	.4 KMPV RESTORE CFG Protocol	18
	8.2	.5 KMPV START MONITOR Protocol	19
	8.2	.6 KMPV STOP MONITOR Protocol	19
	8.2	.7 KMPV VIEW CFG Protocol	19
	8.3	FORM File (#.403)	19
	8.3	.1 KMPV EDIT CONFIGURATION Form	19
	8.3	.2 KMPV VIEW CONFIGURATION Form	20
	8.3	.3 Database Integration Agreements (IAs)	20
9	Glo	bal Variables	20
10	Sec	urity	20
	10.1	Mail Group	
	10.2	Remote Systems	
	10.3	Archiving	21
	10.4	Interfacing	21
	10.5	Electronic Signatures	21
	10.6	Security Menus and Options	21
	10.7	Security Keys	21
	10.8	File Security	21
	10.9	References	21
11	Tro	ubleshooting	22
		List of Figures	
		List of Figures	
Fig	ure 1: V	SM CONFIGURATION File (#8969)—Data Dictionary	5
Fig	ure 2: V	SM MONITOR DEFAULTS file (#8969.02)—Data Dictionary	7
Fig	ure 3: V	SM CACHE TASK LOG file (#8969.03)—Data Dictionary	8
		TCM Usage of ^KMPTMP	
Fig	ure 5: V	STM Usage of ^KMPTMP	9

Figure 6: KMPV VSM MANAGEMENT Option	14
Figure 7: KMPV VTCM DATA TRANSMISSION Option	14
Figure 8: KMPV VSTM DATA TRANSMISSION Option	14
Figure 9: KMPV-CLIENT-SRV Option	14
Figure 10: KMPV MANAGEMENT List Template	17
Figure 11: KMPV DELETE DATA Protocol	18
Figure 12: KMPV EDIT CFG Protocol	18
Figure 13: KMPV MANAGEMENT MENU	18
Figure 14: KMPV RESTORE CFG Protocol	18
Figure 15: KMPV START MONITOR Protocol	
Figure 16: KMPV STOP MONITOR Protocol	19
Figure 17: KMPV VIEW CFG Protocol	19
Figure 18: KMPV EDIT CONFIGURATION Form	19
Figure 19: KMPV VIEW CONFIGURATION Form	20
Figure 20: VSM Database Integration Agreements (IAs)	
Figure 21: KMPVOPS Security Key	21
List of Tables	
List of Tables	
Table 1: Documentation symbol descriptions	vii
Table 2: VSM CONFIGURATION file (#8969)—Field Descriptions	5
Table 3: VSM MONITOR DEFAULTS file (#8969.02)—Field Descriptions	7
Table 4: VSM CACHE TASK LOG file (#8969.03)—Field Descriptions	8
Table 5: VTCM Routines	10
Table 6: VSTM Routines	10
Table 7: VSM Utility Routines	11
Table 8: Caché Task Manager Task Values	15
Table 9: VSM Required Packages	16

Orientation

How to Use this Manual

The purpose of this guide is to provide instructions for use and maintenance of the Veterans Health Information Systems and Technology Architecture (VistA) Capacity and Performance Engineering (CPE) VistA System Monitor (VSM) 1.0 software.

Throughout this manual, advice and instructions are offered regarding the use of the VSM software and the functionality it provides for Veterans Health Information Systems and Technology Architecture (VistA) software products.

Intended Audience

The intended audience of this manual is the following stakeholders:

- Enterprise System Engineering (ESE)—System engineers and Capacity Management personnel responsible for enterprise capacity planning and system architecture.
- Information Resource Management (IRM)—System administrators and Capacity Management personnel at Department of Veterans Affairs (VA) sites who are responsible for computer management and system security on the VistA M Servers.
- Product Development (PD)—VistA legacy development teams.
- Product Support (PS).

Disclaimers

Software Disclaimer

This software was developed at the Department of Veterans Affairs (VA) by employees of the Federal Government in the course of their official duties. Pursuant to title 17 Section 105 of the United States Code this software is *not* subject to copyright protection and is in the public domain. VA assumes no responsibility whatsoever for its use by other parties, and makes no guarantees, expressed or implied, about its quality, reliability, or any other characteristic. We would appreciate acknowledgement if the software is used. This software can be redistributed and/or modified freely provided that any derivative works bear some notice that they are derived from it, and any modified versions bear some notice that they have been modified.

Documentation Disclaimer

This manual provides an overall explanation of using the VistA System Monitor (VSM) 1.0 software; however, no attempt is made to explain how the overall VistA programming system is integrated and maintained. Such methods and procedures are documented elsewhere. We suggest you look at the various VA Internet and Intranet SharePoint sites and websites for a general orientation to VistA. For example, visit the Office of Information and Technology (OI&T) Product Development (PD) Intranet Website.



DISCLAIMER: The appearance of any external hyperlink references in this manual does *not* constitute endorsement by the Department of Veterans Affairs (VA) of this Website or the information, products, or services contained therein. The VA does *not* exercise any editorial control over the information you find at these locations. Such links are provided and are consistent with the stated purpose of this VA Intranet Service.

Documentation Conventions

This manual uses several methods to highlight different aspects of the material:

• Various symbols are used throughout the documentation to alert the reader to special information. Table 1 gives a description of each of these symbols:

Table 1: Documentation symbol descriptions

Symbol	Description
1	NOTE / REF: Used to inform the reader of general information including references to additional reading material.
A	CAUTION / RECOMMENDATION / DISCLAIMER: Used to caution the reader to take special notice of critical information.

- Descriptive text is presented in a proportional font (as represented by this font).
- Conventions for displaying TEST data in this document are as follows:
 - The first three digits (prefix) of any Social Security Numbers (SSN) begin with either "000" or "666".
 - Patient and user names are formatted as follows:
 - <*APPLICATION NAME/ABBREVIATION/NAMESPACE*>PATIENT,<*N*>
 - <APPLICATION NAME/ABBREVIATION/NAMESPACE>USER,<N>

Where "<*APPLICATION NAME/ABBREVIATION/NAMESPACE*>"is defined in the Approved Application Abbreviations document and "<*N*>" represents the first name as a number spelled out or as a number value and incremented with each new entry.

For example, in VSM (KMPV) test patient and user names would be documented as follows:

- KMPVPATIENT, ONE or KMPVUSER, ONE
- KMPVPATIENT,TWO or KMPVUSER,TWO
- KMPVPATIENT, THREE or KMPVUSER, THREE
- KMPVPATIENT,14 or KMPVUSER,14
- Etc.

- "Snapshots" of computer online displays (i.e., screen captures/dialogues) and computer source code is shown in a *non*-proportional font and may be enclosed within a box.
 - User's responses to online prompts are **bold** typeface and highlighted in yellow (e.g., <<u>Enter</u>). The following example is a screen capture of computer dialogue, and indicates that the user should enter two question marks:

Select Primary Menu option: ??

- o Emphasis within a dialogue box is **bold** typeface and highlighted in blue (e.g., **STANDARD LISTENER: RUNNING**).
- o Some software code reserved/key words are **bold** typeface with alternate color font.
- References to "<Enter>" within these snapshots indicate that the user should press the Enter key on the keyboard. Other special keys are represented within <> angle brackets. For example, pressing the PF1 key can be represented as pressing <PF1>.
- o Author's comments are displayed in italics or as "callout" boxes.



NOTE: Callout boxes refer to labels or descriptions usually enclosed within a box, which point to specific areas of a displayed image.

- This manual refers to the M programming language. Under the 1995 American National Standards Institute (ANSI) standard, M is the primary name of the MUMPS programming language, and MUMPS is considered an alternate name. This manual uses the name M.
- All uppercase is reserved for the representation of M code, variable names, or the formal name of options, field/file names, and security keys (e.g., the XUPROGMODE security key).



NOTE: Other software code (e.g., Delphi/Pascal and Java) variable names and file/folder names can be written in lower or mixed case (e.g., CamelCase).

Documentation Navigation

This document uses Microsoft[®] Word's built-in navigation for internal hyperlinks. To add **Back** and **Forward** navigation buttons to the toolbar, do the following:

- 1. Right-click anywhere on the customizable Toolbar in Word (*not* the Ribbon section).
- 2. Select **Customize Quick Access Toolbar** from the secondary menu.
- 3. Select the drop-down arrow in the "Choose commands from:" box.
- 4. Select **All Commands** from the displayed list.
- 5. Scroll through the command list in the left column until you see the **Back** command (green circle with arrow pointing left).
- 6. Select/Highlight the **Back** command and select **Add** to add it to your customized toolbar.
- 7. Scroll through the command list in the left column until you see the **Forward** command (green circle with arrow pointing right).
- 8. Select/Highlight the **Forward** command and select **Add** to add it to the customized toolbar.
- 9. Select **OK**.

You can now use these **Back** and **Forward** command buttons in the Toolbar to navigate back and forth in the Word document when selecting hyperlinks within the document.



NOTE: This is a one-time setup and is automatically available in any other Word document once you install it on the Toolbar.

How to Obtain Technical Information Online

Exported VistA M Server-based software file, routine, and global documentation can be generated using Kernel, MailMan, and VA FileMan utilities.



NOTE: Methods of obtaining specific technical information online is indicated where applicable under the appropriate section.

Help at Prompts

VistA M Server-based software provides online help and commonly used system default prompts. Users are encouraged to enter question marks at any response prompt. At the end of the help display, you are immediately returned to the point from which you started. This is an easy way to learn about any aspect of VistA M Server-based software.

Obtaining Data Dictionary Listings

Technical information about VistA M Server-based files and the fields in files is stored in data dictionaries (DD). You can use the List File Attributes option on the Data Dictionary Utilities menu in VA FileMan to print formatted data dictionaries.



REF: For details about obtaining data dictionaries and about the formats available, see the "List File Attributes" section in the "File Management" section in the *VA FileMan Advanced User Manual*.

Assumptions

This manual is written with the assumption that the reader is familiar with the following:

- VistA computing environment:
 - o Kernel—VistA M Server software
 - o VA FileMan data structures and terminology—VistA M Server software
- Microsoft[®] Windows environment
- M programming language

Reference Materials

Readers who wish to learn more about VSM should consult the following:

- VistA System Monitor (VSM) Installation Guide
- VistA System Monitor (VSM) User Manual
- VistA System Monitor (VSM) Technical Manual (this manual)
- Capacity and Performance Engineering (CPE) website (for more information on CPE services). This site contains other information and provides links to additional documentation.

VistA documentation is made available online in Microsoft[®] Word format and in Adobe[®] Acrobat Portable Document Format (PDF). The PDF documents *must* be read using the Adobe[®] Acrobat Reader, which is freely distributed by Adobe[®] Systems Incorporated at: http://www.adobe.com/

VistA documentation can be downloaded from the VA Software Document Library (VDL): http://www.va.gov/vdl/



REF: See the VistA System Monitor (VSM) manuals on the VDL.

VistA documentation and software can also be downloaded from the Product Support (PS) Anonymous Directories.

1 Process Overview

The VistA System Monitor (VSM) 1.0 software is intended to collect Caché and VistA metrics related to system capacity and business usage. The package is made up of multiple collectors. The first collectors to be deployed are the following:

- VistA Timed Collection Monitor (VTCM)—Collects Caché metrics at regularly scheduled intervals such that they can be used in conjunction with metrics gathered via other deployed collection tools.
- VistA Storage Monitor (VSTM)—Collects storage metrics for each database once daily.

This data is used for understanding VistA systems as they relate to the infrastructure on which they are deployed.

As a general rule, any VSM monitor follows the following process (specifics for any monitor are listed below separately):

- 1. Metrics are either collected on a periodic basis or aggregated to a similar time period. This allows metrics to be used in conjunction with those from other tools already being used within the VA.
- 2. Metrics are transferred from the VistA sites to the VSM national database via MailMan on a regular periodic schedule. This schedule is determined by the type of monitor, but in most cases is nightly.
- 3. Metrics are purged from the VistA sites quickly. Under normal situations the metrics are deleted from the sites upon receipt of the acknowledgment from the VSM national database. A purge is run at the start of any VSM monitor that deletes any data older than the time period specified in the VSM CONFIGURATION file for that monitor.

In some cases, the collection routine may need to run on each separate node of a VistA system. This is accomplished via a task in the Caché Task Manager. The Caché Task Manager executes a routine each morning immediately after midnight. This routine looks at each monitor in the VSM CONFIGURATION file. It first checks to see if the monitor's ONOFF value is set to **ON**. If so, it checks to see if the monitor has an entry in its CACHE DAILY TASK field (#1.03). This field represents the name of the collection routine for a given monitor. If there is an entry in this field then the Caché task executes the RUN linetag of this routine.

1.1 VistA Timed Collection Monitor (VTCM) Specific Process

1.1.1 VTCM Monitor—Starting and Stopping

1.1.1.1 Starting VTCM Monitor

To start the VTCM monitor use the VSM MANAGEMENT menu option and choose the **STRT** action. Choose **VTCM** at the monitor prompt. This does two things:

- 1. Sets the ONOFF field to **ON** in the VSM CONFIGURATION file for the VTCM entry.
- Schedules the TaskMan task, which is responsible for transferring the metrics to the VSM national database. This TaskMan task is scheduled using the values found in the TASKMAN SCHEDULE FREQUENCY and TASKMAN SCHEDULE START fields in the VSM CONFIGURATION file for the VTCM entry.



NOTE: Collection of metrics does *not* commence until the next execute of the Caché Task Manager task.

1.1.1.2 Stopping VTCM Monitor

To stop the VTCM monitor use the VSM MANAGEMENT menu option and choose the **STOP** action. Choose **VTCM** at the monitor prompt. This does two things:

- 1. Sets the ONOFF field to **OFF** in the VSM CONFIGURATION file for the VTCM entry.
- 2. Un-schedules the TaskMan task started in the **STRT** action.

The collector stops upon its next iteration as it checks the ONOFF value before each collection.



NOTE: If the collection job is stopped via the VSM MANAGEMENT option then metric collection does *not* restart until 12:01 AM on the following day. If needed, collection can be started manually, but *must* be done on each separate node. To do this, enter the following at a programmer prompt on each node:

D RUN^KMPVVTCM

1.1.2 VTCM Metric Collection

VTCM Metrics are collected via the routine KMPVVTCM. This routine reads values from the ^CacheTemp.SysMetrics global on a periodic basis as specified by the COLLECTION INTERVAL field in the VSM CONFIGURATION file entry for VTCM. The default value is every five minutes.

Metrics are stored for the day in the 'KMPTMP("KMPV","VTCM" global by day (\$H), node and time slot.



REF: For details on file metrics, see Section 1.1.3.

The collection routine (KMPVVTCM) runs until the start of a new day (new \$H value) unless the ONOFF value is set to **OFF** via the VSM MANAGEMENT application. Upon the next iteration of the collection process the monitor checks this value and quits if turned **OFF**. If the monitor is turned **OFF** and back **ON**, metric collection does *not* resume until the start of the next day when the Caché Task Manager starts that day's collection.

1.1.3 VTCM Metric Transmission

Separately, TaskMan kicks off a routine to mail the collected metrics to the VSM national database.

- 1. TaskMan executes the **SEND^KMPVVTCM** routine.
 - a. The time of this task is set via the TASKMAN SCHEDULE START field in the VSM CONFIGURATION file entry. By default it runs at 1AM. This task:
 - i. Kills (deletes) any date older than the time period specified in the DAYS TO KEEP DATA field in the VSM CONFIGURATION file.
 - ii. Sends an informational mail message to Capacity and Performance Engineering (CPE) support for data older than 1 day but less than the kill date, and then sends/resends the data
 - iii. Sends data for prior day.
- 2. For each day that data is sent an entry is made in ^KMPTMP("KMPV","VTCM",DLY,\$H) with the mail message number.
- 3. The data for each day is deleted once an ACK mail message is received from the CPE server.

1.2 VistA Storage Monitor (VSTM) Specific Process

1.2.1 VSTM Monitor—Starting and Stopping

1.2.1.1 Starting VSTM Monitor

To start the VSTM monitor use the VSM MANAGEMENT menu option and choose the **STRT** action. Choose **VSTM** at the monitor prompt. This does two things:

- 1. Sets the ONOFF field to **ON** in the VSM CONFIGURATION file for the VSTM entry.
- Schedules the TaskMan task, which is responsible for transferring the metrics to the VSM national database. This TaskMan task is scheduled using the values found in the TASKMAN SCHEDULE FREQUENCY and TASKMAN SCHEDULE START fields in the VSM CONFIGURATION file for the VSTM entry.



NOTE: Collection of metrics does *not* commence until the next execute of the Caché Task Manager task.

1.2.1.2 Stopping VSTM Monitor

To stop the VSTM monitor use the VSM MANAGEMENT menu option and choose the **STOP** action. Choose **VSTM** at the monitor prompt. This does two things:

- 1. Sets the ONOFF field to **OFF** in the VSM CONFIGURATION file for the VTCM entry.
- 2. Un-schedules the TaskMan task started in the **STRT** action.

The collector stops upon its next iteration as it checks the ONOFF value before each collection.



NOTE: The VSTM collector runs only one time per day when started by the Caché Task Manager KMPVRUN task. Collections begin on the day following the day the monitor is turned **ON**.

1.2.2 VSTM Metric Collection

VSTM Metrics are collected via the KMPVVSTM routine. This routine executes a portion the %FreeCnt routine logic to collect storage metrics for each database.

Metrics are collected on the 15th and last day of the month and stored for the day in the ^KMPTMP("KMPV","VSTM" global by day (\$H) and node.



REF: For details on file metrics, see Section 1.2.3.

The collection routine (KMPVVSTM) runs once upon being started by the Caché Task Manager if the ONOFF value is set to **ON**.

1.2.3 VSTM Metric Transmission

Separately, TaskMan kicks off a routine to mail the collected metrics to the VSM national database.

- 1. TaskMan executes the **SEND^KMPVVSTM** routine.
 - a. The time of this task is set via the TASKMAN SCHEDULE START field in the VSM CONFIGURATION file entry. By default it runs at 1AM. This task:
 - i. Kills (deletes) any date older than the time period specified in the DAYS TO KEEP DATA field in the VSM CONFIGURATION file.
 - ii. Sends an informational mail message to CPE support for data older than 1 day but less than the kill date, and then sends/resends the data.
 - iii. Sends data for prior day.
- 2. For each day that data is sent an entry is made in ^KMPTMP("KMPV","VSTM",DLY,\$H) with the mail message number.
- 3. The data for each day is deleted once an ACK mail message is received from the CPE server.

2 Files

This section lists the files associated with the VistA System Monitor (VSM) application. The files are:

- VSM CONFIGURATION File (#8969); Global: ^KMPV(8969)
- VSM MONITOR DEFAULTS File (#8969.02); Global: ^KMPV(8969.02)
- VSM CACHE TASK LOG File (#8969.03); Global: ^KMPV(8969.03)
- <u>^KMPTMP("KMPV","VTCM"—Temporary Data Storage</u>

2.1 VSM CONFIGURATION File (#8969); Global: ^KMPV(8969

2.1.1 Data Dictionary

Figure 1: VSM CONFIGURATION File (#8969)—Data Dictionary

2.1.2 VSM CONFIGURATION File Field Descriptions Field Descriptions

Table 2: VSM CONFIGURATION file (#8969)—Field Descriptions

Field Name	Field Number	Description	
MONITOR KEY	8969, .01	Two to four Letter acronym used to identify specific monitor	
ONOFF	8969, .02	Flag used to stop or continue monitor collection	
FULL NAME	8969, .03	Descriptive name for specific monitor. Usually related to the Monitor Key. For example, VTCM = VistA Timed Collection Monitor.	
VERSION	8969, .04	Current version of VSM software.	
INSTALL DATE	8969, .05	Date current version of software was installed.	
DAYS TO KEEP DATA	8969, 1.01	Number of days that unsent data is allowed to remain in ^KMPTMP("KMPV" before the purge routine kills it. Limited to 3 days. Data older than this value is deleted; regardless of the reason it has <i>not</i> been sent to the national database, in order to assure global does <i>not</i> grow unchecked.	
COLLECTION INTERVAL	8969, 1.02	The number in minutes used to gather or aggregate metrics. Monitors that collect metrics on a periodic basis use this value to	

Field Name	Field Number	Description	
		wait between collections. Monitors that collect data continuously use this value for aggregation of metrics.	
CACHE DAILY TASK	8969, 1.03	The name of the routine, if applicable, to start each days collection. The Caché Task Manager calls the RUN linetag of this routine at the start of every day. This allows collection tasks to run on each node of a VistA system - front end and back end.	
ALLOW TEST SYSTEM	8969, 1.04	If set to "Yes" this allows the monitors to run on test systems. Otherwise monitors exit if the current UCI is <i>not</i> set as "PROD" per ^%ZOSF("UCI").	
TASKMAN SCHEDULE FREQUENCY	8969, 1.05	The value used to automatically reschedule the TaskMan tasks (e.g., 1D or 1W).	
TASKMAN SCHEDULE START	8969, 1.06	The time each monitor's TaskMan task should be scheduled. (e.g., T+1@0001).	
TASKMAN OPTION	8969, 1.07	The OPTION file entry used by TaskMan to schedule the daily background jobs.	
LAST START TIME	8969, 2.01	Time last TaskMan task was started for a specific monitor.	
LAST STOP TIME	8969, 2.02	Time last TaskMan task completed for a specific monitor.	
LAST RUN TIME	8969, 2.03	Time in seconds from start to completion of most recent run for a specific monitor TaskMan task.	
NATIONAL DATA EMAIL ADDRESS	8969, 3.01	Email address used to send metric data to the national Capacity and Performance Engineering (CPE) database.	
NATIONAL SUPPORT EMAIL ADDRESS	8969, 3.02	Email address used to send messages to the CPE VistA CP mail group.	
VSM CFG EMAIL ADDRESS	8969, 3.03	Email address used to send data other than daily metrics to CPE national database.	
LOCAL SUPPORT EMAIL ADDRESS	8969, 3.04	Optional email address for local support personnel. If present, any email that would be sent to the national support group also goes to the local support group.	

2.2 VSM MONITOR DEFAULTS File (#8969.02); Global: ^KMPV(8969.02

2.2.1 Data Dictionary

Figure 2: VSM MONITOR DEFAULTS file (#8969.02)—Data Dictionary

```
CROSS REFERENCED BY: MONITOR KEY(B)

^KMPV(8969.02,D0,0) = (#.01) MONITOR KEY [1F] ^ (#.02) DAYS TO KEEP DATA [2N] ^
(#.03) COLLECTION INTERVAL [3N] ^ (#.04) CACHE DAILY TASK [4F] ^
(#.05) ALLOW TEST SYSTEM [5S] ^ (#.06) TASKMAN SCHEDULE FREQUENCY [6F] ^
(#.07) TASKMAN SCHEDULE START [7F] ^ (#.08) TASKMAN OPTION [8F] ^
KMPV(8969.02,D0,1) = (#1.01) NATIONAL DATA EMAIL ADDRESS [1F] ^
(#1.02) NATIONAL SUPPORT EMAIL ADDRESS [2F] ^ (#1.03) VSM CFG EMAIL ADDRESS [3F] ^
```

2.2.2 Field Descriptions

Table 3: VSM MONITOR DEFAULTS file (#8969.02)—Field Descriptions

Field Name	Field Number	Description	
MONITOR KEY	8969.02, .01	Two to four letter acronyms used to identify specific monitor.	
DAYS TO KEEP DATA	8969.02, .02	Number of days that unsent data is allowed to remain in ^KMPTMP("KMPV" before the purge routine kills it. Limited to 3-7 days. Data older than this value is deleted; regardless of the reason it has <i>not</i> been sent to the national database, in order to assure global does <i>not</i> grow unchecked.	
COLLECTION	8969.02, .03	The number in minutes used to gather or aggregate metrics. Monitors that collect metrics on a periodic basis use this value to wait between collections. Monitors that collect data continuously use this value for aggregation of metrics.	
CACHE DAILY TASK	8969.02, .04	The name of the routine, if applicable, to start each days collection. The Caché Task Manager calls the RUN linetag of this routine at the start of every day. This allows collection tasks to run on each node of a VistA system - front end and back end.	
ALLOW TEST SYSTEM	8969.02, .05	If set to "Yes" this allows the monitors to run on test systems. Otherwise monitors exit if the current UCI is <i>not</i> set as "PROD" per ^%ZOSF("UCI").	
TASKMAN SCHEDULE FREQUENCY	8969.02, .06	The value used to automatically reschedule the TaskMan tasks. (e.g., 1D or 1W).	
TASKMAN SCHEDULE START	8969.02, .07	The time each monitor's TaskMan task should be scheduled. (e.g., T+1@0001).	
TASKMAN OPTION	8969.02, .08	The OPTION file (#19) entry used by TaskMan to schedule the daily background jobs.	
NATIONAL DATA EMAIL ADDRESS	8969.02, 1.01	Email address used to send metric data to the national CPE database.	
NATIONAL	8969.02, 1.02	Email address used to send messages to the CPE VistA CP mail	

Field Name	Field Number	Description
SUPPORT EMAIL ADDRESS		group.
VSM CFG EMAIL ADDRESS	8969.02, 1.03	Email address used to send data other than daily metrics to CPE national database.

2.3 VSM CACHE TASK LOG File (#8969.03); Global: ^KMPV(8969.03

2.3.1 Data Dictionary

Figure 3: VSM CACHE TASK LOG file (#8969.03)—Data Dictionary

```
CROSS REFERENCED BY: DATE(B)

INDEXED BY: DATE & NODE (C)

^KMPV(8969.03,D0,0) = (#.01) DATE [1D] ^ (#.02) NODE [2F] ^ (#.03) VTCM RUNTIME [3D]

^ (#.04) VSTM RUNTIME [4D] ^
```

2.3.2 Field Descriptions

Table 4: VSM CACHE TASK LOG file (#8969.03)—Field Descriptions

Field Name	Field Number	Description	
DATE	8969.02, .01	Run date for specific monitor as started from The Caché Task Manager.	
NODE	8969.02, .02	Specific node on which collection routine was run.	
VTCM RUNTIME	8969.02, .03	Time the VistA Timed Collection Monitor (VTCM) was started in VA FileMan datetime format.	
VSTM RUNTIME	8969.02, .04	Time the VistA Storage Monitor (VSTM) was started in VA FileMan datetime format.	

8

2.4 ^KMPTMP("KMPV","VTCM"—Temporary Data Storage

^KMPTMP is a temporary global used by multiple KMP packages including KMPV – VistA System Manager.



CAUTION: This global is not in VA FileMan format and should not be journaled.

The following sections document how the VTCM and VSTM monitors use this global.

2.4.1 VTCM Usage of ^KMPTMP

Figure 4: VTCM Usage of ^KMPTMP

```
^KMPTMP("KMPV", "VTCM", "DLY", $H) = MSG Number until ACK rec'd
     $H: Internal format for date
     MSG Number: The number of the MailMan message that sent this day's data. Node
will be deleted upon receipt of ACK from the VSM national server
^KMPTMP("KMPV","VTCM","DLY",$H,Node,TimeSlot)=DATA
$H: Internal format for date
Node: Name of node from which the data was collected
TimeSlot: $H time format representing the time interval of the collected data (data
is aggregated to number of seconds for the configured COLLECTION INTERVAL).
Ex. 300 is 5 minutes after midnight - or 00:05AM
         1200 is 20 minutes after midnight - or 00:20AM
         86100 is 1435 minutes past midnight - or 11:35PM
DATA: "^" delimited string containing collected metric values.
Global References ^ Global References Per Second ^ Global Sets and Kills ^ Logical
Requests ^ Physical Block Reads ^ Physical Block Writes ^ Processes ^ Routine
Commands ^ Routine Lines ^ Routine References ^ SMH Memory Used ^ SMH PageUsed ^
CSP Sessions ^ Cache Efficiency ^ ECP Client Bytes Per Second ^ ECP Server Bytes
Per Second ^ Paging ^ Page Space ^ Physical Memory
^KMPTMP("KMPV","VTCM","TRANSMIT" -- runtime only node used to pass data to MailMan
```

2.4.2 VSTM Usage of ^KMPTMP

Figure 5: VSTM Usage of ^KMPTMP

```
^KMPTMP("KMPV","VSTM","DLY",$H) = MSG Number until ACK rec'd
$H: Internal format for date
MSG Number: The number of the MailMan message that sent this day's data. Node
will be
deleted upon receipt of ACK from the VSM national server

^KMPTMP("KMPV","VSTM","DLY",$H,Node,Database)=DATA
$H: Internal format for date
Node: Name of node from which the data was collected
Database: Name of the Caché database. (ex: mgr, vaa, cache, rou, etc.)

DATA: "^" delimited string containing collected metric values.
Max Size ^ Size ^ Available ^ %Free ^ Disk Free

^KMPTMP("KMPV","VSTM","TRANSMIT" -- runtime only node used to pass data to MailMan
```

3 Routines

This section lists the routines and line tags for VistA System Monitor (VSM) monitors. The routines include:

- VistA Timed Collection Monitor (VTCM) Specific Routines
- VistA Storage Monitor (VSTM) Specific Routines
- VSM Utility Routines

3.1 VistA Timed Collection Monitor (VTCM) Specific Routines

Table 5: VTCM Routines

Routine	Line Tag	Description
KMPVVTCM	Collect Caché Metrics for the VistA Timed Collection Monitor	
	RUN	Collect metrics per configured interval and store in ^KMPTMP("KMPV","VTCM","DLY". Called via the Caché Task Manager.
	SEND	Format daily metric data to for MailMan transmission.
	TRANSMIT	Transmit daily data to the VSM national server.

3.2 VistA Storage Monitor (VSTM) Specific Routines

Table 6: VSTM Routines

Routine	Line Tag	Description
KMPVVSTM	Collect Caché Metrics for the VistA Timed Collection Monitor	
	RUN	Entry point. Determines if metrics should be collected for that day.
	METRICS	Collect metrics per configured interval and store in ^KMPTMP("KMPV","VSTM","DLY". Called via the Caché è Task Manager.
	SEND	Format daily metric data to for MailMan transmission.
	TRANSMIT	Transmit daily data to the VSM national server.

August 2016

3.3 VSM Utility Routines

Table 7: VSM Utility Routines

Routine	Line Tag	Description
KMPVCSRV	VSM Server Routine for VistA Functions	
	EN	Server routine entry point.
	ACK	Receive acknowledge VSM receipt of VTCM data – delete from local node.
	GETSTAT	Returns current status of VSM.
	RESEND	Resend data for one or more monitors.
	SETCFG()	Change VSM configuration via national server change request.
	KMPUPDEF	Update VSM MONITOR DEFAULTS file. Optionally apply defaults to VSM CONFIGURATION file.
	CTMLOG	Returns the run history recorded in the VAM CACHE TASK LOG file.
KMPVCCFG	FG VSM Configuration Functions	
	CFGARR(KMPVMKEY,KMPVCFG ,KMPVFLAG	Return configuration by monitor in array.
	GETDEF(KMPVMKEY,KMPVDEF, KMPVFLAG)	Return default configuration in array.
	CFGSTR(KMPVMKEY,KMPVFLAG)	Return configuration in "^" delimited string.
	GETVAL(KMPVMKEY,KMPVFLD,KMPVFILE,KMPVFLAG)	Retrieve value from VSM CONFIGURATION or VSM MONITOR DEFAULTS files.
	SETONE(KMPVMKEY,KMPVFNAM ,KMPVNVAL,KMPVERR,KMPVLOG)	Set a value into the VSM CONFIGURATION file.
	SETVALS(KMPVMKEY,KMPVFVAL, KMPVERR,KMPVLOG)	Set multiple values into the VSM CONFIGURATION file.
	RESTCFG(KMPVMKEY)	Restore default configuration to VSM CONFIGURATION file.
	STRSTP(KMPVMKEY,KMPVSTIME)	Record run time values.
	SYSCFG()	Return system configuration values.
	MONSTAT(KMPVTEXT)	Return status information for all configured monitors.
	USERNAME(KMPVDUZ)	Return users name from DUZ.
	PROD()	Return "Prod" if production, "Test" otherwise.
KMPVCBG	VSM Background Utility Functions	

Routine	Line Tag	Description
	MONLIST(KMPVML)	Return list of configured Monitors.
	STARTMON(KMPVMKEY)	Schedule transmission task in TaskMan and set ONOFF to ON.
	STOPMON(KMPVMKEY)	Un-schedule transmission task in TaskMan and set ONOFF to OFF.
	RESCH(KMPVMKEY,KMPVERR)	Reschedule transmission task in TaskMan.
	DESCH(KMPVMKEY,KMPVERR)	De-schedule transmission task in TaskMan.
	CANMESS(MTYPE,KMPVMKEY, KMPVSITE,KMPVD)	Repeatable, configured mail messages.
	SUPMSG(KMPVTEXT)	Send email to national and local support mail groups.
	DBAMSG(KMPVTEXT)	Send email to local support mail group.
	CFGMSG(KMPVRQNAM)	Send configuration data to update Location Table at National VSM Database.
	PURGEDLY(KMPVMKEY)	Purge any data older than VSM CONFIURATION file specifies.
	KMPVTSK(NAMESPACE)	Creates a Task in the Caché Task Manager to start the VSM collection driver each day.
		Passing no namespace attempts to \$ZDEFNSP.
KMPVLM	List Manager Functions	
	EN	Main entry point for VSM MANAGEMENT menu option.
	HDR	Header Code.
	INIT	Initialize variables and list array.
	BUILD	Build array with collector status information.
	STARTMON	Supports List Manager protocol 'STRT Start Monitor'.
	STOPMON	Supports List Manager protocol 'STOP Stop Monitor'.
	VIEWCFG	Supports List Manager protocol 'VIEW View CFG'.
	EDITCFG	Supports List Manager protocol 'EDIT Edit CFG'.
	RESTCFG	Supports List Manager protocol 'REST Restore CFG'.

Routine	Line Tag	Description
	KILL(KMPVMKEY)	Supports List Manager protocol 'DEL Delete Data.
	PICKMON()	Supports selection of Monitor Type for List Manager functions.
	REFRESH	Refresh display.
	HELP	Help code.
	EXIT	Exit code.
	EXPND	Expand code.
KMPVRUN	VSM Caché Task Manager Driver	
	RUN	Loop VSM CONFIGURATION file and run collection routine for monitors set to "ON".
	CLEANUP	Purge old data in VSM CACHE TASK LOG file and release lock.
	ERR	Error trap as routine is called from Caché Task Manage.
KMPVPST1	Post Install Routine for KMPV*1.0*0	
		Creates entries in the VSM CONFIGURATION and VSM MONITOR DEFAULT files.

4 Exported Options

This section lists the options in the Option file (#19) exported with VistA System Monitor (VSM).

4.1 KMPV VSM MANAGEMENT Option

Figure 6: KMPV VSM MANAGEMENT Option

NAME: KMPV VSM MANAGEMENT MENU TEXT: VSM MANAGEMENT

TYPE: run routine CREATOR: L,J
LOCK: KMPVOPS ROUTINE: EN^KMPVLM

UPPERCASE MENU TEXT: VSM MANAGEMENT

4.2 KMPV VTCM DATA TRANSMISSION Option

Figure 7: KMPV VTCM DATA TRANSMISSION Option

NAME: KMPV VTCM DATA TRANSMISSION MENU TEXT: KMPV VTCM DATA TRANSMISSION

TYPE: run routine CREATOR: L,J

DESCRIPTION: Daily background job to send VTCM metrics to national database.

This job should be scheduled to run during non-peak hours.

ROUTINE: SEND^KMPVVTCM SCHEDULING RECOMMENDED: YES

KEEP FROM DELETING: Yes UPPERCASE MENU TEXT: KMPV VTCM DATA TRANSMISSION

4.3 KMPV VSTM DATA TRANSMISSION Option

Figure 8: KMPV VSTM DATA TRANSMISSION Option

NAME: KMPV VSTM DATA TRANSMISSION MENU TEXT: KMPV VSTM DATA TRANSMISSION

TYPE: run routine CREATOR: L,J

PACKAGE: CAPACITY MANAGEMENT - VSM

DESCRIPTION: Background job to send VSTM metrics to national database. This

job should be scheduled to run during non-peak hours.

ROUTINE: SEND^KMPVVSTM SCHEDULING RECOMMENDED: YES

KEEP FROM DELETING: Yes

UPPERCASE MENU TEXT: KMPV VSTM DATA TRANSMISSION

4.4 KMPV-CLIENT-SRV Option

Figure 9: KMPV-CLIENT-SRV Option

NAME: KMPV-CLIENT-SRV MENU TEXT: KMPV-CLIENT-SRV

TYPE: server CREATOR: L,J

ROUTINE: KMPVCSRV SERVER ACTION: RUN IMMEDIATELY

SERVER MAIL GROUP: CPE-CP-SUPPORT

SUPRESS BULLETIN: NO (DEFAULT) SEND A BULLETIN

UPPERCASE MENU TEXT: KMPV-CLIENT-SRV

4.5 KMPV MANAGEMENT MENU

For details on this menu, see Section 8.2.3.

5 Archiving

Data is removed nightly from the sites. There are no special archiving procedures required with the VistA System Monitor (VSM) 1.0 software.

6 Application Programming Interfaces (APIs)

There are no VSM callable routines, entry points, or Application Programming Interfaces (APIs) that can be called by other software.

7 External Relationships

7.1 Caché Task Manager

<u>Table 8</u> details the parameters used to enter the task in the Caché Task Manager to start the monitors on each node. This is created by running the KMPVTSK line tag of the KMPVCBG routine. The person running this line tag/routine *must* have either of the following roles:

- %All
- %Manager

Table 8: Caché Task Manager Task Values

Field	Entry	
Task Name:	KMPVRUN	
Description:	Start VSM Collection Drivers	
Namespace to run task in:	Default routine namespace - usually 3-letter site acronym (e.g., CTX for Central Texas)	
Task type:	RunLegacyTask	
ExecuteCode:	D RUN^KMPVRUN	
Task priority:	Priority Normal	
Run task as this user:	Username of person setting up task	
Open output file when task is running?	No	
Output file:	Leave blank	
Reschedule task after system restart?	Yes	

The task should be scheduled to run once daily at 1:00 AM.

7.2 Dependencies

7.2.1 Packages

VSM is dependent on the following packages:

Table 9: VSM Required Packages

Software	Version	Patch Information
Kernel	8.0	Fully patched
Kernel Toolkit	7.3	Fully patched
VA FileMan	22.0	Fully patched
MailMan	8.0	Fully patched

8 Internal Relationships

This section lists entries in various VistA files necessary for the operation of VistA System Monitor (VSM).

8.1 LIST TEMPLATE File (#409.61)

8.1.1 KMPV MANAGEMENT List Template

Figure 10: KMPV MANAGEMENT List Template

```
NAME: KMPV MANAGEMENT
                                       TYPE OF LIST: PROTOCOL
RIGHT MARGIN: 80
                                     TOP MARGIN: 9
    BOTTOM MARGIN: 13
                                          OK TO TRANSPORT?: NOT OK
                                          PROTOCOL MENU: KMPV MANAGEMENT MENU
     USE CURSOR CONTROL: YES
     SCREEN TITLE: VSM MANAGEMENT
                                          ALLOWABLE NUMBER OF ACTIONS: 2
                                          HIDDEN ACTION MENU: VALM HIDDEN ACTIONS
    AUTOMATIC DEFAULTS: YES
ITEM NAME: Monitor
                                       COLUMN: 2
    WIDTH: 8
                                         DISPLAY TEXT: Monitor
                                       COLUMN: 12
ITEM NAME: Status
    WIDTH: 6
                                         DISPLAY TEXT: Status
    DEFAULT VIDEO ATTRIBUTES: R
ITEM NAME: LastTransmission
                                       COLUMN: 20
    WIDTH: 20
                                         DISPLAY TEXT: Last Transmission
                                       COLUMN: 42
ITEM NAME: DLY
    WIDTH: 5
                                         DISPLAY TEXT: DLY
    DEFAULT VIDEO ATTRIBUTES: B
ITEM NAME: COMP
                                       COLUMN: 49
    WIDTH: 5
                                          DISPLAY TEXT: COMP
    DEFAULT VIDEO ATTRIBUTES: B
ITEM NAME: NextTransmission
                                       COLUMN: 56
    WIDTH: 20
                                         DISPLAY TEXT: Next Transmission
ITEM NAME: Monitor
                                       COLUMN: 2
    WIDTH: 8
                                         DISPLAY TEXT: Monitor
ITEM NAME: Status
                                       COLUMN: 12
    WIDTH: 6
                                         DISPLAY TEXT: Status
    DEFAULT VIDEO ATTRIBUTES: R
ITEM NAME: LastTransmission
                                       COLUMN: 20
    WIDTH: 20
                                         DISPLAY TEXT: Last Transmission
ITEM NAME: DLY
                                       COLUMN: 42
    WIDTH: 5
                                         DISPLAY TEXT: DLY
    DEFAULT VIDEO ATTRIBUTES: B
ITEM NAME: COMP
                                       COLUMN: 49
    WIDTH: 5
                                          DISPLAY TEXT: COMP
    DEFAULT VIDEO ATTRIBUTES: B
ITEM NAME: NextTransmission
                                       COLUMN: 56
    WIDTH: 20
                                          DISPLAY TEXT: Next Transmission
    DEFAULT VIDEO ATTRIBUTES: R
EXIT CODE: D EXIT^KMPVLM
                                     HEADER CODE: D HDR^KMPVLM
HELP CODE: D HELP^KMPVLM
                                     ENTRY CODE: D INIT^KMPVLM
```

8.2 PROTOCOL File (#101)

8.2.1 KMPV DELETE DATA Protocol

Figure 11: KMPV DELETE DATA Protocol

NAME: KMPV DELETE DATA

TYPE: action

CREATOR: L,J

ENTRY ACTION: D KILL^KMPVLM TIMESTAMP: 63419,42385

8.2.2 KMPV EDIT CFG Protocol

Figure 12: KMPV EDIT CFG Protocol

NAME: KMPV EDIT CFG ITEM TEXT: Edit CFG

TYPE: action CREATOR: L,J

ENTRY ACTION: D EDITCFG^KMPVLM TIMESTAMP: 63417,36668

8.2.3 KMPV MANAGEMENT MENU Protocols

The following protocols on the KMPV MANAGEMENT MENU are stored in the PROTOCOL File (#101):

Figure 13: KMPV MANAGEMENT MENU

NAME: KMPV MANAGEMENT MENU ITEM TEXT: KMPV MANAGEMENT MENU

TYPE: menu CREATOR: L,J
COLUMN WIDTH: 26 MNEMONIC WIDTH: 6
ITEM: KMPV START MONITOR MNEMONIC: STRT

SEQUENCE: 1

ITEM: KMPV STOP MONITOR MNEMONIC: STOP

SEQUENCE: 2

ITEM: KMPV VIEW CFG MNEMONIC: VIEW

SEQUENCE: 3

ITEM: KMPV DELETE DATA MNEMONIC: DEL

SEQUENCE: 6

ITEM: KMPV RESTORE CFG MNEMONIC: REST

SEQUENCE: 5

ITEM: KMPV EDIT CFG MNEMONIC: EDIT

SEQUENCE: 4

HEADER: D SHOW^VALM MENU PROMPT: Select Action

TIMESTAMP: 63452,46698

8.2.4 KMPV RESTORE CFG Protocol

Figure 14: KMPV RESTORE CFG Protocol

NAME: KMPV RESTORE CFG ITEM TEXT: Restore CFG

TYPE: action CREATOR: L,J

ENTRY ACTION: D RESTCFG^KMPVLM TIMESTAMP: 63417,35298

8.2.5 KMPV START MONITOR Protocol

Figure 15: KMPV START MONITOR Protocol

NAME: KMPV START MONITOR ITEM TEXT: Start Monitor

TYPE: action CREATOR: L,J

ENTRY ACTION: D STARTMON^KMPVLM TIMESTAMP: 63417,37931

8.2.6 KMPV STOP MONITOR Protocol

Figure 16: KMPV STOP MONITOR Protocol

NAME: KMPV STOP MONITOR ITEM TEXT: Stop Monitor

TYPE: action CREATOR: L,J

ENTRY ACTION: D STOPMON^KMPVLM TIMESTAMP: 63417,37989

8.2.7 KMPV VIEW CFG Protocol

Figure 17: KMPV VIEW CFG Protocol

NAME: KMPV VIEW CFG ITEM TEXT: View CFG

TYPE: action CREATOR: L,J

ENTRY ACTION: D VIEWCFG^KMPVLM TIMESTAMP: 63417,38175

8.3 FORM File (#.403)

8.3.1 KMPV EDIT CONFIGURATION Form

Figure 18: KMPV EDIT CONFIGURATION Form

NAME: KMPV EDIT CONFIGURATION READ ACCESS: @

WRITE ACCESS: @ CREATOR: 520791172

DATE CREATED: OCT 14, 2014@14:28 DATE LAST USED: OCT 31, 2014@12:04

PRIMARY FILE: 8969 DISPLAY ONLY: NO FORM ONLY: NO COMPILED: YES

PAGE NUMBER: 1 PAGE COORDINATE: 1,1

PAGE NAME: Page 1

BLOCK NAME: KMPV EDIT CFG

BLOCK COORDINATE: 1,1

BLOCK NAME: KMPV EDIT TITLE

BLOCK ORDER: 2

BLOCK COORDINATE: 16,1

TYPE OF BLOCK: DISPLAY

19

8.3.2 KMPV VIEW CONFIGURATION Form

Figure 19: KMPV VIEW CONFIGURATION Form

```
NAME: KMPV VIEW CONFIGURATION
                                       READ ACCESS: @
WRITE ACCESS: @
                                     CREATOR: 520791172
DATE CREATED: OCT 15, 2014@08:48
                                   DATE LAST USED: OCT 31, 2014@12:03
PRIMARY FILE: 8969
                                     DISPLAY ONLY: YES
FORM ONLY: NO
                                     COMPILED: YES
PAGE NUMBER: 1
                                       PAGE COORDINATE: 1,1
PAGE NAME: Page 1
BLOCK NAME: KMPV VIEW CFG
                                       BLOCK ORDER: 1
BLOCK COORDINATE: 1,1
                                     TYPE OF BLOCK: DISPLAY
BLOCK NAME: KMPV VIEW TITLE
                                       BLOCK ORDER: 2
BLOCK COORDINATE: 16,1
                                     TYPE OF BLOCK: DISPLAY
```

8.3.3 Database Integration Agreements (IAs)

Figure 20: VSM Database Integration Agreements (IAs)

```
This version of VSM software is dependent on the following Integration Agreements
IA#:
     Name-Components:
                                                           Usage:
      -----
                                                           -----
10097 %ZOSV-GETENV, $$0S, $$VERSION
                                                           Supported
10112 VASITE-$$SITE
                                                           Supported
10060 New Person File
                                                           Supported
1966
      DBIA1966
                                                           Subscription
2734
      MESSAGE & MAILBOX UTILITIES API-$$NETNAME
                                                           Supported
10073 MAILMAN: Message Body Access, including Servers-REC
                                                          Supported
6247
      Direct KMPV read to KMPTMP
                                                           Private
```

9 Global Variables

There are no VSM global variables.

10 Security

10.1 Mail Group

Optionally, sites can enter a local email address in the Edit CFG action under the VSM MANAGEMENT option. The local support mail group receives the same informational email messages that go to national support mail group.



NOTE: There are no bulletins or alerts.

10.2 Remote Systems

Data collected includes only system metrics. None of the following data is collected:

- Personal Identification Information (PII)
- Personal Health Information (PHI)
- Patient, clinician, or financial data collected

Examples of data collected include:

- Number of global reads/writes per time period.
- Amount of storage space used by the system in question.

Data transmissions:

- VTCM data is sent to the CPE national database on a nightly basis.
- VSTM data is transmitted on the 15th and last day of each month. This data is transmitted using standard MailMan messages.

Receipt of data is confirmed with a MailMan message sent in response. This message triggers the site to delete the data at the site.

10.3 Archiving

For VSM archiving information, see Section 5.

10.4 Interfacing

VSM software operates on standard VistA software and hardware.

10.5 Electronic Signatures

VSM does *not* use of electronic signatures.

10.6 Security Menus and Options

VSM does *not* distribute any security menus or options.

10.7 Security Keys

The KMPVOPS security key is needed to access the VSM Management Menu. This key should only be given to those who manage VSM.

Figure 21: KMPVOPS Security Key

NAME: KMPVOPS DESCRIPTIVE NAME: VSM OPERATIONS LOCK

10.8 File Security

For a list of files exported with VSM, see Section 2.

10.9 References

For a list of document and other references, see the "Reference Materials" section.

11 Troubleshooting

There are no known issues or anomalies related to the VistA System Monitor (VSM) 1.0 software.

This software is intended to run automatically in the background and should require no operational support under normal operations. However, for those times where support is needed there are two mechanisms within this package to provide such functionality:

- Local Operational Support: There is a List Manager Application installed with this package that allows the local support staff to:
 - Start and stop monitors
 - View operational parameters
 - o Configure operational parameters
 - o Delete all locally stored data in case of emergency



REF: These actions are documented in Section 2 in the *VistA System Monitor (VSM) User Manual*.

• National CPE Support: Additionally, this software has the capability to receive requests for the same functions via MailMan messages from the CPE VSM Support group.